

V240m

Traditional POS



The V240m, part of the Verifone Engage portfolio, combines the latest in features, functionality, and performance into one efficient and cost-effective solution. Boasting a large, 3.5" color touch display, more memory, faster processor and multiple connectivity options, this full-function portable payment device makes doing business on the go easy. Whether merchants are looking to accept basic payment transactions or explore more advanced capabilities like paying with points, digital couponing, and other value-added services, the V240m makes it possible. Ideal for pay-at-the-table, curbside delivery, kiosks and line-busting.



**Convenience
Stores**



**Government
Departments**



Hotels



Logistics



Retail Chains



Supermarkets



and more.*

Verifone

*Customizable solutions available

FEATURES



New intuitive user interface makes it easy to navigate



Corning® Gorilla® Glass 3 technology minimizes screen scratches and breakage



Accepts all payment types: NFC/contactless, mobile wallets, EMV, magstripe



EMV-ready and fully compliant with the latest PCI 5.X requirements



Utilizes the power of Verifone Connect for point-of-sale customization, device management, security, and support



SPECIFICATIONS

PROCESSOR	600 MHz, Cortex A9 32-bit RISC processor, 1500 MIPS
MEMORY	384 MB (256 MB Flash, 128 MB SDRAM), microSD
DISPLAY	3.5" HVGA capacitive touch screen, Corning® Gorilla® Glass 3 technology
KEYPAD	backlit keypad
PRINTER	30 lps, 40 mm paper roll
CARD SLOTS	2 SAM, 1 SIM
CARD READERS (MAGSTRIPE/ IC/ CONTACTLESS)	Triple track MSR: ISO 7810, 7811, 7813 Smart card reader: EMVCo-approved
CONNECTIVITY	Single USB connector for 1 host/client, separate charging connector
COMMUNICATIONS	Four standard options: 2G; 3G; Bluetooth 4.2 BLE + 2.4 GHz WiFi; or 3G + Bluetooth 4.2 BLE + 2.4 GHz WiFi
ENVIRONMENT	Operating temperature: 0° to 50° C (32° to 122° F); storage temperature: -20° to 60° C (-4° to 140° F); relative humidity: 5% to 90%, non-condensing
BATTERY	3.7 V/2450 mAh Li-ion
POWER SUPPLY	PSU: 100-240 VAC w/ output DC 5 V, 1 amp
CERTIFICATIONS	PCI PTS 5.X-approved
DIMENSIONS & WEIGHT	162.9mm L x 75.3mm W x 53.4mm H, 274g (9.66oz)



EFT Solutions Limited

Member of EFT Solutions Holdings Limited (Stock Code : 8062)

Workshops B1 & B3, 11/F, Yip Fung Industrial Building,
28-36 Kwai Fung Crescent, Kwai Chung, N.T., Hong Kong